



The BL Series is a Type I, Low Proximity Hood for use over 400° and 600°F cooking surface temperatures. This model offers the ability to underhang the hood by 4.5" from the front of the cooking surface.

Fully Integrated Package

CaptiveAire sells this hood as a stand-alone appliance to be integrated into a kitchen ventilation application, or provided as part of a FULLY INTEGRATED PACKAGE designed by CaptiveAire and pre-engineered for optimum performance. The package consists of the hood, an integral utility cabinet, factory pre-wired electrical controls, and a listed fire suppression system. Other options include a listed exhaust fan, a listed make-up air unit and listed, factory-built ductwork.

Advantages

- **Exhaust Rates:** Low exhaust CFMs required for hood model.
- **ETL Listed:** ETL Listed for use over 400°F and 600°F cooking surface temperatures. ETL Listed to US and Canadian safety standards, ETL Sanitation Listed and built in accordance with NFPA 96.
- **Construction:** Fabricated of Type 430 stainless steel, #3 or #4 polish, on all exposed surfaces. Optional type 304 stainless steel available. Sloped grease drain system with removable 1/2 pint cup for easy cleaning.
- **Convenient Design:** Space saving, compact design uses limited kitchen space. Pre-punched hanging angles on each end of the hood and additional set provided for hoods longer than 12'.
- **Grease Extraction:** Fitted with baffle filters, removable for cleaning. Optional Captrate Combo®, Captrate Solo® are available. Sloped grease drain system with removable 1/2 pint cup for easy cleaning.

Performance

MODEL	TYPE		MIN. SUPPLY CFM/FT.	MAX. SUPPLY CFM/FT.
BL	Wall Hood	400°F - Cooking Surface--Ovens, Steamers, Kettles Open-Burner Ranges, Griddles, Fryers	114	N/A
BL	Wall Hood	600°F - Gas Charbroilers, Electric Charbroilers, Woks	160	N/A

Options

Rear Make-Up Air Plenum: Provides make-up air for the kitchen and is discharged below cooking equipment. Provides required clearance from limited combustibles per NFPA 96 Standards.

Enclosure Panels: Constructed of stainless steel. Sized to extend from hood top to ceiling, enclosing pipe and hanging parts.

Roof Top Package: Combination ETL Listed exhaust/supply air unit with factory prewired and mounted motors, trunkline and curb vented on exhaust side.

Separate Exhaust and/or Make-Up Air Fans: ETL Listed single exhaust fans and supply-air fans and curbs available.

Fire Suppression System: UL 300 fire suppression system.

Certifications

The BL Model has been certified by ITS. This certification mark indicates that the product has been tested to and has met the minimum requirements of a widely recognized (consensus) U.S. and Canadian products safety standard, that the manufacturing site has been audited, and that the applicant has agreed to a program of periodic factory follow-up inspections to verify continued performance.

Models BL are ETL Listed under file number 3054804-001 and complies with UL710, ULC710 and ULC-S646 Standards.

